






DLM1330R



DLM1315R



DLM1308R



FEATURES:

BODY

Solid aluminium alloy, High quality body structure, without enameled painting.

Diffuser

Satined glass diffuser.

Others

- High corrosion resistant capability
- Stainless steel alloy screws
- Power supply: 100 - 220V-240V/50Hz
- Heat resistant and solid conduct wiring
- European standard of EN 60598

Model No.	DLM1305R	DLM1308R	DLM1312R
Type of LED	SMD	SMD	SMD
Power	5W LED	8W LED	12W LED
Power Factor	>90	>90	>90
Color Temp.	3000 - 6500K	3000 - 6500K	3000 - 6500K
CRI	≥85	≥85	≥85
Beam Angle	120°	120°	120°
Luminous Flux	380LM	610LM	960LM
Temp. in Working	-20°C +50°C	-20°C +50°C	-20°C +50°C
Dimension	55x68mm	75x85mm	94x97mm
Life Span	35000 - 45000Hrs		

Model No.	DLM1315R	DLM1320R	DLM1330R
Type of LED	SMD	SMD	SMD
Power	15W LED	20W LED	30W LED
Power Factor	>90	>90	>90
Color Temp.	3000 - 6500K	3000 - 6500K	3000 - 6500K
CRI	≥85	≥85	≥85
Beam Angle	120°	120°	120°
Luminous Flux	1200LM	1600LM	2600LM
Temp. in Working	-20°C +50°C	-20°C +50°C	-20°C +50°C
Dimension	114x109mm	139x125mm	190x145mm
Life Span	35000 - 45000Hrs		