



FEATURES:

- Surface wall marking luminaire
- Narrow beam angle

Body

- Made of die cast aluminium
- Powder coated finish
- White, Black, & Grey

Diffuser

- Polycarbonate, Uv-stabilised

Others

- ◆ Built in LED drive
- ◆ High quality COB LED chip
- ◆ Heat resistant and solid conduct wiring
- ◆ Ideal for interior, exterior lighting
- ◆ European standard of EN 60598

Available:




IP65

CE NOM

SUPERINTENDENCIA DE ELECTRICIDAD Y COMBUSTIBLES SEC

EN EC

B-W004D ()**



Model No.	B-W004D-3	B-W004D-4	B-W004D-6	B-W004D-12
Power	3W	4W	6W	12W
Size	80x80x75mm	80x80x75mm	160x160x120mm	160x160x120mm
Type of LED	COB	COB	COB	COB
Luminous Flux	100LM/W	100LM/W	100LM/W	100LM/W
Color Temp.	2700-6500K	2700-6500K	2700-6500K	2700-6500K
Voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V
Power Factor	0.95	0.95	0.95	0.95
Beam Angle	10°/ 15°/ 30°/ 60°	10°/ 15°/ 30°/ 60°	10°/ 15°/ 30°/ 60°	10°/ 15°/ 30°/ 60°
CRI	>80	>80	>80	>80
Working Temp.	-20-40°C	-20-40°C	-20-40°C	-20-40°C
Protection	IP65	IP65	IP65	IP65
Life	50000Hrs			
Warranty	Three Year			

