



### FEATURES:

- Recessed mounted downlight

#### Body

- Made of die-cast aluminium
- Powder coated finish
- White, Silver, Chrome, Black

#### Diffuser

- Clear glass / Opal Polycarbonate

#### Reflector

- Anodized aluminium

#### Others







- ◆ Aluminium structured heat sink
- ◆ High efficient COB LED chip
- ◆ Dimmable Dali / TRIAC 0 - 10V Available on request
- ◆ Heat resistant and solid conduct wiring
- ◆ Ideal for interior lighting
- ◆ European standard of EN 60598

Model No.	SW-DL015-(**)	SW-DL015-(**)	SW-DL015-(**)	SW-DL015-(**)	SW-DL015-(**)
Power	3W COB LED	12W COB LED	20W COB LED	30W COB LED	40W COB LED
	5W COB LED	15W COB LED	25W COB LED	36W COB LED	45W COB LED
	7W COB LED	-	-	-	50W COB LED
	9W COB LED	-	-	-	-
Dimension	Dia:95xH:63/73mm	Dia:115xH:116mm	Dia:142xH:131mm	Dia:160xH:123mm	Dia:160xH:133mm Dia:182xH:133mm
Voltage	AC160V-245V	AC160V-245V	AC160V-245V	AC160V-245V	AC160V-245V
Power Factor	>0.95	>0.95	>0.95	>0.95	>0.95
Color Temp.	2700K - 6500K	2700 - 6500K	2700 - 6500K	2700 - 6500K	2700 - 6500K
CRI	≥80	≥80	≥80	≥80	≥80
Luminous Flux	110-120LM/W	110-120LM/W	110-120LM/W	110-120LM/W	110-120LM/W
Temp. in Working	-20°C +50°C	-20°C +50°C	-20°C +50°C	-20°C +50°C	-20°C +50°C
Driver	Isolated	Isolated	Isolated	Isolated	Isolated
Beam Angle	15° 25° 45° 60° 80° 90°				
Life Span	45000 - 50000Hrs				

Available:



SW-DL015-3W/5W/7W/9W      SW-DL015-12W/15W      SW-DL015-20W/25W      SW-DL015-30W/36W      SW-DL015-40W/45W      SW-DL015-50W



### SW-DL015-(\*\*)



### SW-DL015-(\*\*)



### SW-DL015-(\*\*)

