

FEATURES:

- Ceiling mounted LED Track light

Body

- Made of aluminium, Uv-stabilized, powder coated
- White, Black, Silver finish.

Reflector

- Anodized aluminium

Diffuser

- Clear safety glass

Others

- ◆ Aluminium structured heat sink for better heat dissipation
- ◆ High efficient COB LED chip
- ◆ Heat resistant and solid conduct wiring
- ◆ Ideal for Office, Public areas
- ◆ European standard of EN 60598



BT3030-(**)



Model No.	BT3030-10M	BT3030-15	BT3030-20/25	BT3030-30
Power	10W LED Max	15W LED	20W / 25W LED	30W LED
Type of LED	COB	COB	COB	COB
Dimension	Dia: 75x110mm	Dia: 90x145mm	Dia: 90x145mm	Dia: 90x145mm
Voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V
Power Factor	>0.95	>0.95	>0.95	>0.95
Color Temp.	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K
CRI	≥80	≥80	≥80	≥80
Luminous Flux	100LM/W	100LM/W	100LM/W	100LM/W
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C
Angle	15° 24° 40° 60°	15° 24° 40° 60°	15° 24° 40° 60°	15° 24° 40° 60°
Protection	IP44	IP44	IP44	IP44
Life Span	50000Hrs			

Aluminium Track Size with End Cap: 1000x30x30mm (Custom made size available on request)

BT3030-(**)



ALUMINIUM TRACK & ACCESSORIES

INSTALLATION

