

FEATURES

Surface mounted LED Panel light
Suitable for concrete ceiling, bulkhead ceiling

BODY

Housing and frame made of extruded aluminium white, grey and natural aluminium finish.

Diffuser

Uv-stabilized, anti yellowing fiber opal, prismatic diffuser with thermal shock resistant.

Reflector


Wide beam LED reflector

Others

- Aluminium mounting clamp for easy installation
- Brilliant lighting effect with high efficiency
- Dimmable Dalli / TRIAC 0 - 10V Available on request (Maximum Wattage: 40W)
- Heat resistant and solid conductor terminal connector
- High quality HF LED drive
- Ideal for interior installation
- European standard of EN 60598



SW-SM002/3030



SW-SM002/6060



SW-SM002/30120



Model No.	SW-SM002/3030	SW-SM002/3060	SW-SM002/6060	SW-SM002/30120	SW-SM002/60120
Type of LED	SMD-EPISTAR	SMD-EPISTAR	SMD-EPISTAR	SMD-EPISTAR	SMD-EPISTAR
Power	24W	24W/30W	36W/40W/48W/50W/54W	36W/48W/54W	48W/54W/72W
Input Voltage	AC85-265V/50-60Hz	AC85-265V/50-60Hz	AC85-265V/50-60Hz	AC85-265V/50-60Hz	AC85-265V/50-60Hz
Power Factor	>90	>90	>90	>90	>90
Color Temp.	3000 - 6500K	3000 - 6500K	3000 - 6500K	3000 - 6500K	3000 - 6500K
CRI	≥80	≥80	≥80	≥80	≥80
Beam Angle	120°	120°	120°	120°	120°
Luminous Flux	90-100LM/W	90-100LM/W (24W) 100-110LM/W (30W)	80-90LM/W (36W) 90-100LM/W (40W) 110LM/W (48/54W)	80-90LM/W (36W) 100-110LM/W (48/54W)	80-90LM/W (48/54W) 100-110LM/W (72W)
Temp. in Working	-10°C +50°C	-10°C +50°C	-10°C +50°C	-10°C +50°C	-10°C +50°C
Driver	Isolated	Isolated	Isolated	Isolated	Isolated
Dimension	300x300mm	300x600mm	600x600mm	300x1200mm	600x1200mm
Life Span			50000Hrs		

Hanging Accessories (Order Code: SK10)



Mounting Clip for Aluminium Dampa Ceiling (Order Code: RD10)

