



FEATURES:

- Recessed mounted LED spotlight

Body

- Made of die-cast aluminium, Uv-stabilized, Electro coated powder coating.
- White, Black and Silver finish.

Reflector

- Anodized aluminium

Others

- ◆ High quality retrofit lamp in GU5.3, GU10 Base
- ◆ Aluminium structured heat sink for better heat dissipation (SW-WL025A/B/C/D).
- ◆ High efficient COB LED
- ◆ Heat resistant and solid conduct wiring
- ◆ Ideal for Office, Public areas
- ◆ European standard of EN 60598

Available:



IP44






Retrofit LED Specification

Model No.	SW-WLR025A/B/C/D		
Power	3W LED	5W LED	7W LED
Type of LED	COB	COB	COB
Dimension	Dia:79xH: 80mm	Dia:79xH: 80mm	Dia:79xH: 80mm
Voltage	AC85-265V	AC85-265V	AC85-265V
Power Factor	>0.95	>0.95	>0.95
Color Temp.	2700K - 6500K	2700K - 6500K	2700K - 6500K
CRI	≥80	≥80	≥80
Luminous Flux	100-110LM/W	100-110LM/W	100-110LM/W
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C
Angle	38°	38°	38°
Protection	IP44	IP44	IP44
Life Span		50000Hrs	

SW-WLR025A/B/C/D-3W

SW-WLR025A/B/C/D-5W

SW-WLR025A/B/C/D-7W



SW-WLR025A



SW-WLR025B



SW-WLR025C



SW-WLR025D



SW-WL025A




SW-WL025B



SW-WL025C



SW-WL025D



Model No.	SW-WL025A/B/C/D		
Power	7W LED	10W LED	12W LED
Type of LED	COB	COB	COB
Dimension	Dia:79xH:95mm	Dia:79xH:105mm	Dia:79xH:115mm
Voltage	AC85-265V	AC85-265V	AC85-265V
Power Factor	>0.95	>0.95	>0.95
Color Temp.	2700K - 6500K	2700K - 6500K	2700K - 6500K
CRI	≥80	≥80	≥80
Luminous Flux	100-110LM/W	100-110LM/W	100-110LM/W
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C
Angle	10/20/30/45°	10/20/30/45°	10/20/30/45°
Protection	IP44	IP44	IP44
Life Span	50000Hrs		

CUSTOMIZED DESIGN



INSTALLATION

