



### FEATURES:

Recessed LED luminaire for exposed T-Grid and Dampa false ceilings

### BODY

Made of cold rolled sheet steel, sturdy white powder coated  
Comination with Uv-resistant polyester film for uniform lighting distribution

### Reflector



High gloss white powder coated cold rolled steel sheet

### Others

- Aluminium mounting clamp for easy installation
- Brilliant lighting effect with high efficiency
- Dimmable Dalli / TRIAC 0 - 10V available on request
- Heat resistant and solid conductor terminal connector
- High quality HF LED drive
- Suitable for lighting applications in indoor areas where higher degree of protection like hospitals, offices, laboratories etc.
- European standard of EN 60598



### DLT22-(\*\*)



Model No.	DLT22-30	DLT22-40	DLT22-50	DLT22-60	DLT22-80
Type of LED	SMD 2835	SMD 2835	SMD 2835	SMD 2835	SMD 2835
Power	30W	40W	50W	60W	80W
Input Voltage	AC85-265/50-60Hz	AC85-265/50-60Hz	AC85-265/50-60Hz	AC85-265/50-60Hz	AC85-265/50-60Hz
Power Factor	>95	>95	>95	>95	>95
Color Temp.	3000K - 6500K	3000K - 6500K	3000K - 6500K	3000K - 6500K	3000K - 6500K
CRI	≥80	≥80	≥80	≥80	≥80
Beam Angle	120°	120°	120°	120°	120°
Luminous Flux	110LM/W	110LM/W	110LM/W	110LM/W	110LM/W
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C
Driver	Isolated	Isolated	Isolated	Isolated	Isolated
Protection	IP44	IP44	IP44	IP44	IP44
Size	595x595x100mm	595x595x100mm	595x595x100mm	1195x595x100mm	1195x595x100mm
Life Span			50000Hrs		