



FEATURES:

- Recessed mounted LED Downlight
- SMD LED 2835

Body

- Made of die-cast aluminium with surface powder coated.
- White and Black finish

Diffuser

- Opal Polystyrene / PMMA, thermal shock resistant

Reflector

- Glare free white reflector

Others

- ◆ Aluminium structured heat sink
- ◆ High efficient SMD LED chip
- ◆ Dimmable Dalli / TRIAC 0 - 10V Available on request
- ◆ Heat resistant and solid conduct wiring
- ◆ Ideal for interior lighting
- ◆ European standard of EN 60598

Available: 3000K 3500K 4000K 4500K 5000 - 5500K 6000 - 6500K




BFL2031-7W




BFL2031-30W




BFL2031-7W




BFL2031-12W




BFL2031-15W



BFL2031-20W



BFL2031-25/30W



Model No.	BFL2031-7W	BFL2031-12W	BFL2031-15W	BFL2031-20W	BFL2031-25W	BFL2031-30W
Power	7W LED	12W LED	15W LED	20W LED	25W LED	30W LED
LED Type	SMD	SMD	SMD	SMD	SMD	SMD
Dimension	Dia:90xH:41mm	Dia:120xH:41mm	Dia:145xH:41mm	Dia:175xH:41mm	Dia:220xH:41mm	Dia:220xH:41mm
Voltage	AC100-265V/50-60Hz	AC100-265V/50-60Hz	AC100-265V/50-60Hz	AC100-265V/50-60Hz	AC100-265V/50-60Hz	AC100-265V/50-60Hz
Power Factor	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95
Color Temp.	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K
CRI	≥80	≥80	≥80	≥80	≥80	≥80
Luminous Flux	100LM/W	100LM/W	100LM/W	100LM/W	100LM/W	100LM/W
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C
Beam Angle	120°	120°	120°	120°	120°	120°
Protection	IP44	IP44	IP44	IP44	IP44	IP44
Life Span	50000Hrs					