



FEATURES:

- Recessed mounted downlight
- SMD LED chip by CREE / OSRAM

Body

- Made of die-cast aluminium with surface powder coated.
- Black, White finish

Diffuser

- Opal Polycarbonate, thermal shock resistant

Reflector

- Anodized aluminium with glare control

Others

- ◆ Aluminium structured heat sink
- ◆ High efficient SMD LED chip
- ◆ Heat resistant and solid conduct wiring
- ◆ Ideal for interior lighting
- ◆ European standard of EN 60598



Available:	3000K	3500K	4000K	4500K	5000 - 5500K	6000 - 6500K
------------	-------	-------	-------	-------	--------------	--------------



BFL2001R



BFL2001Q



BFL2001R-6W	BFL2001R-10W	BFL2001R-20W	BFL2001Q-15W	BFL2001Q-20W

Model No.	BFL2001R	BFL2001R	BFL2001R	BFL2001Q	BFL2001Q
Wattage	6W LED	10W LED	20W LED	15W LED	20W LED
LED Type	SMD	SMD	SMD	SMD	SMD
Dimension	Ø90xH47mm	Ø119xH50mm	Ø175xH56mm	145x145xH55mm	170x170xH55mm
Voltage	AC220V-240V	AC220V-240V	AC220V-240V	AC220V-240V	AC220V-240V
Power Factor	>0.90	>0.90	>0.90	>0.90	>0.90
Color Temp.	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K
CRI	≥80	≥80	≥80	≥80	≥80
Luminous Flux	100LM/W	100LM/W	100LM/W	100LM/W	100LM/W
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C
Protection	IP44	IP44	IP44	IP54	IP54
Dimmable	TRIAC/0-10V/PWM/Dali Dimmable (Order code = / Dali Dim / PWM Dim)				
Life Span	50000Hrs				
Remarks	Custom wattage available on request.				